

KONTROL - KUMANDA KABLOLARI - ÇELİK TEL EKİRLİ
CONTROL CABLES - GALVANIZED STEEL WIRE BRAIDED

ÇELİK ÖRGÜLÜ KONTROL KABLOSU

300/500 V.

S.P.KODU ORDER CODE	KESİTİMİ CROSS SECTION mm ²	Dİ ÇAP OVERALL DIA. mm	BAKIR AĞIRLIĞI COPPER WEIGHT Kg/Km	YAKL. AĞIRLIK APP. WEIGHT Kg/Km
1 mm²				
43010002	2 x 1	8,8	49,0	11
43010003	3 G 1	9,2	58,0	138
43010004	4 G 1	10,1	73,0	174
43010005	5 G 1	11,0	86,0	202
43010006	6 G 1	11,8	99,0	232
43010007	7 G 1	12,9	112,0	260
43010008	8 G 1	13,8	127,0	296
43010009	9 G 1	14,6	134,0	332
43010010	10 G 1	15,1	141,0	344
43010012	12 G 1	15,6	176,0	416
43010014	14 G 1	16,3	198,0	430
43010016	16 G 1	17,1	217,0	492
43010018	18 G 1	17,9	249,0	556
43010020	19 G 1	19,0	256,0	580
43010024	20 G 1	19,0	264,0	592
43010025	24 G 1	21,0	316,0	734
43010027	25 G 1	21,1	332,0	760
43010030	27 G 1	21,4	374,0	818
43010032	30 G 1	22,0	394,0	932
43010034	34 G 1	23,8	422,0	989
43010036	36 G 1	23,8	446,0	998
43010037	37 G 1	24,8	455,0	1014
43010040	40 G 1	26,0	568,0	1141
43010041	41 G 1	26,0	582,0	1154
43010046	46 G 1	27,6	642,0	1232
43010050	50 G 1	28,4	698,0	1288
43010061	61 G 1	30,7	842,0	1442
43010065	65 G 1	32,0	908,0	1508
43210075	75 G 1	33,4	1048,0	1664
43010090	90 G 1	35,4	1252,0	1896
2,5 mm²				
43025002	2 x 2,5	11,3	82,0	188
43025003	3 G 2,5	11,7	112,0	238
43025004	4 G 2,5	13,0	144,0	284
43025005	5 G 2,5	14,2	178,0	336
43025006	6 G 2,5	15,5	204,0	384
43025007	7 G 2,5	16,9	228,0	438
43025008	8 G 2,5	18,2	258,0	489
43025010	10 G 2,5	20,3	312,0	660
43025012	12 G 2,5	20,5	370,0	758
43025014	14 G 2,5	21,6	416,0	884
43025016	16 G 2,5	23,0	466,0	946
43025018	18 G 2,5	24,2	518,0	1052
43025020	20 G 2,5	25,8	573,0	1138
43025024	24 G 2,5	28,8	860,0	1342
43025025	25 G 2,5	29,1	892,0	1376
43025027	27 G 2,5	29,3	964,0	1503
43025030	30 G 2,5	30,4	1056,0	1652
43025034	34 G 2,5	32,7	1172,0	1890
43025041	41 G 2,5	35,2	1472,0	2284
43025046	46 G 2,5	37,2	1578,0	2467
43025050	50 G 2,5	38,2	1662,0	2676
43025061	61 G 2,5	41,4	1984,0	3082

S.P.KODU ORDER CODE	KESİTİMİ CROSS SECTION mm ²	Dİ ÇAP OVERALL DIA. mm	BAKIR AĞIRLIĞI COPPER WEIGHT Kg/Km	YAKL. AĞIRLIK APP. WEIGHT Kg/Km
1,5 mm²				
43015002	2 x 1,5	9,6	62,0	145
43015003	3 G 1,5	10,1	75,0	171
43015004	4 G 1,5	11,0	93,0	198
43015005	5 G 1,5	12,0	110,0	233
43015006	6 G 1,5	13,2	128,0	280
43015007	7 G 1,5	14,2	152,0	314
43015008	8 G 1,5	15,4	170,0	346
43015009	9 G 1,5	16,4	185,0	380
43015010	10 G 1,5	16,8	206,0	442
43015012	12 G 1,5	17,1	244,0	504
43015014	14 G 1,5	18,2	282,0	560
43015016	16 G 1,5	19,2	312,0	604
43015018	18 G 1,5	20,2	356,0	705
43015019	19 G 1,5	21,3	368,0	726
43015020	20 G 1,5	21,3	383,0	772
43015024	24 G 1,5	23,8	437,0	941
43015025	25 G 1,5	24,0	454,0	952
43015027	27 G 1,5	24,0	526,0	1016
43015030	30 G 1,5	25,0	652,0	1091
43015032	32 G 1,5	26,0	694,0	1130
43015034	34 G 1,5	27,1	742,0	1207
43015036	36 G 1,5	27,2	771,0	1264
43015037	37 G 1,5	28,2	785,0	1300
43015040	40 G 1,5	29,2	832,0	1432
43015041	41 G 1,5	29,2	846,0	1458
43015046	46 G 1,5	31,0	949,0	1568
43015050	50 G 1,5	32,0	1041,0	1654
43015061	61 G 1,5	34,7	1246,0	1854
43015065	65 G 1,5	35,7	1318,0	1972
43015075	75 G 1,5	37,4	1532,0	2280
4 mm²				
43040002	2 x 4	13,0	134,0	232
43040003	3 G 4	13,8	176,0	354
43040004	4 G 4	15,4	238,0	427
43040005	5 G 4	16,8	276,0	510
43040006	6 G 4	20,4	357,0	658
43040008	8 G 4	21,7	430,0	734
43040012	12 G 4	24,5	580,0	981
6 mm²				
43060002	2 x 6	14,5	205,0	295
43060003	3 G 6	15,5	247,0	418
43060004	4 G 6	17,2	320,0	576
43060005	5 G 6	19,3	404,0	720
43060007	7 G 6	23,0	502,0	1027
43060012	12 G 6	27,6	905,0	1682
10 mm²				
43100002	2 x 10	18,7	292,0	614
43100003	3 G 10	19,8	374,0	660
43100004	4 G 10	22,0	496,0	898
43100005	5 G 10	24,0	624,0	1086
43100007	7 G 10	29,2	828,0	1520
43100012	12 G 10	34,8	1364,0	2462
16 mm²				
43160003	3 x 16	23,1	562,0	992
43160004	4 G 16	25,2	826,0	1341
43160005	5 G 16	28,2	1058,0	1624
43160007	7 G 16	33,6	1498,0	2076
25 mm²				
43250003	3 x 25	28,4	848,0	1362
43250004	4 G 25	31,5	1174,0	1796
43250005	5 G 25	34,2	1436,0	2164
35 mm²				
43350003	3 x 35	31,6	1152,0	1838
43350004	4 G 35	35,0	1562,0	2286
43350005	5 G 35	38,6	1880,0	2686
50 mm²				
43500003	3 x 50	36,2	1654,0	2604
43500004	4 G 50	40,5	2120,0	3240