

YASSI FLEKS BL KABLolar
FLAT FLEXIBLE CABLES

H03VVH2-F / H05VVH2-F

H03VVH2-F 300/300 V.
H05VVH2-F 300/500 V.

Teknik Bilgiler

H03VVH2-F	TS 9760 HD 21.5
H05VVH2-F	TS 9760 HD 21.5
Çalışma Voltajı H03VVH2-F	300/300 V.
Çalışma Voltajı H05VVH2-F	300/300 V.
Test Gerilimi H03VVH2-F	1200 V.
Test Gerilimi H05VVH2-F	1200 V.
Çalışma Sıcaklığı	-5° C.....+70° C -30° C.....+70° C

Technical Data

H03VVH2-F	TS 9760 HD 21.5
H05VVH2-F	TS 9760 HD 21.5
Operating Voltage H03VVH2-F	300/300 V.
Operating Voltage H05VVH2-F	300/300 V.
Test Voltage H03VVH2-F	1200 V.
Test Voltage H05VVH2-F	1200 V.
Temperature Range	-5° C.....+70° C -30° C.....+70° C

Kablo yapısı

İletken: İnce bakır tellerden bükülmüş iletken HD 383 ve IEC 225 sınıf 5'e uygun

Damar izolesi: İki farklı renkte PVC izoleli tel

Kılıf: PVC

Kullanım alanı

Elektrikli cihazların enerji besleme kabloları olarak ve mekanik darbelerle maruz olmayan yerlerde kullanılırlar.

Cable Structure

Conductor: Fine stranded copper wires. According to HD 383 and IEC 228 class 5

Core insulation: Two different colored insulated wires are sheathed by PVC

Outer Sheath: PVC

Application

They are mainly used as power supply cords for electrical equipments and in places where there is no mechanical stress.



S.P.KODU ORDER CODE	KESİTİMİ CROSS SECTION mm ²	Dİ ÇAP OVERALL DIA. mm	BAKIR AĞIRLIĞI COPPER WEIGHT Kg/Km	YAKLAŞIK AĞIRLIK APP. WEIGHT Kg/Km
H03VVH2-F				
38005002	2 x 0,50	3,3 x 5,6	9,7	33
38007502i	2 x 0,75	3,6 x 6,3	14,1	37
H05VVH2-F				
38007502	2 x 0,75	4,3:7,1	14,2	52
38010002	2 x 1	4,5:7,4	19,1	61